



MATERIAL SAFETY DATA SHEET

Vicinity Manufacturing

145 Church Street
Suite 150
Marietta, GA 30060

**TO LEARN HOW VICINITY CAN SIMPLIFY YOUR
MSDS & COMPLIANCE - CONTACT:**

Vicinity Sales
info@vicinitymanufacturing.com
Telephone: 770.421.2467

VISIT US ON THE WEB AT:
www.vicinitymanufacturing.com

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	D

ATTENTION: This MSDS is created to show you how Vicinity Manufacturing Software can create Material Safety Data Sheets for your organization. This document has been generated directly from Vicinity. The contents and information represent no real product but have been assembled to show you the capabilities of Vicinity.

SECTION 1: PRODUCT IDENTIFICATION

Product Name:	Vicinity Red
Chemical Family:	Petroleum Based Paint Covering
Material Usage:	Industrial Paint Coating

SECTION 2: HAZARDOUS INGREDIENTS

Component	Wt %	Recommended Exposure Limits (TWA)
Petroleum Hydrocarbon Distillate CAS #8008-20-6	10-20%	OSHA PEL: 500 ppm
Petroleum Oil CAS #64741-96-4 and/or #6472-52-5	50-60%	OSHA PEL: Not Established ACGIH TLV: 5 mg/m3 (mists)
Oxidized Aliphatic Hydrocarbon CAS #Not Avail	< 10%	OSHA PEL: 2 mg/m3 (wax fumes)
Ethylene Glycol CAS #107-21-1	< 10%	OSHA PEL: OSHA PEL: 50 ppm ACGIH TLV: ACGIH TLV: 50 ppm
Talc CAS #14807-96-6	< 10%	OSHA PEL: 2 mg/m3 ACGIH TLV: 2 mg/m3

SECTION 3: HEALTH HAZARD INFORMATION

Primary Routes of Entry:

Inhalation, Skin Absorption.

Acute Effects:

Excessive inhalation may produce dizziness, nausea, headache, and incoordination. May cause severe eye irritation and reversible skin irritation. Prolonged skin exposure may cause dermatitis or oil acne.

Breathing mists may cause dizziness or pulmonary irritation.

SECTION 4: FIRST AID MEASURES

Inhalation:

Move victim to fresh air and call emergency medical care. If not breathing, give artificial respiration; if breathing is difficult, give oxygen.

Eye Contact:

Flush eyes with large amounts of water for 15 minutes. Get medical attention.

SECTION 5: FIRE AND EXPLOSION HAZARD DATA

Flash Point:	175 deg F. (COC)
Explosive Limits LEL:	0.6
Explosive Limits UEL:	7.0

Extinguish Media - Small Fires:

Dry chemical, CO2, water spray, or regular foam.

Extinguish Media - Large Fires:

Water spray, fog, or regular foam. Move container from fire area if you can do it without risk. Apply cooling water to sides to containers that are exposed to flames until well after fire is out. Stay away from ends of tanks. For massive fire in cargo area, use unmanned hose holder or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

SECTION 6: HANDLING & STORAGE

PRECAUTIONS FOR HANDLING & STORAGE:

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Keep out of the reach of children.

SECTION 7: PERSONAL PROTECTION

Protective Gloves & Eye Protection:

Wear gloves recommended by glove supplier for protection against materials in Section 2. Wear safety spectacles with unperforated sideshields.

SECTION 8: TRANSPORT INFORMATION

DOT PROPER SHIPPING DESCRIPTION:

Paint and Related Materials, NOIBN

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Color:	RED
Appearance:	Liquid
Odor:	Paint Like Smell
Boiling Point (initial):	>300 deg F.

SECTION 10: OTHER INFORMATION

Disclaimer:

This MSDS represents no actual product. The purpose of this document is to show the highlights and abilities of Vicinity Manufacturing Software for producing an MSDS. To learn how Vicinity can assist your organization for MSDS & Compliance, Formulation or Production, visit us at www.vicinitymanufacturing.com or email us at info@vicinitymanufacturing.com.